# NSN 5930-00-925-3622

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-925-3622

# **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

2.781 inches

#### **Overall Height:**

1.578 inches

#### **Overall Width:**

1.437 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.781 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 9:00 o'clock

## Individual Section Quantity:

2

## Nonturn Device Type:

Tab at 9: 00 o'clock

## **Operating Tempurature Range:**

-65.0/+100.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### **Rotor Through Connection Quantity:**

1 1st section

#### Switch Actuator Indexing Position Quantity:

12 single actuator

#### Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Makes before breaks 1st section front

# NSN 5930-00-925-3622

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load dc at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0