

View Online at <https://aerobasegroup.com/nsn/5930-00-925-5202>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.856 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.312 inches 2nd actuator

Overall Diameter:

1.312 inches

Nonturn Device Radius:

0.531 inches at 5: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 5: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 2nd section rear

Throw Quantity:

4 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor provisions

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

90.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0