

View Online at <https://aerobasegroup.com/nsn/5930-00-925-7419>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

2.310 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.423 inches single actuator

Overall Diameter:

1.000 inches

Nonturn Device Radius:

0.375 inches at 11: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Pin at 11: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 3rd section front

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

3 3rd section

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 1st section rear

Detent Rotational Torque Range:

+1.500/+5.500 inch-pounds single actuator

Contact Load Current Rating:

1.5 amperes resistive load ac at sea level and 750.0 milliamperes inductive load ac at sea level and 300.0 milliamperes lamp load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0