

View Online at <https://aerobasegroup.com/nsn/5930-00-925-7419>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

2.310 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.423 inches single actuator

**Overall Diameter:**

1.000 inches

**Nonturn Device Radius:**

0.375 inches at 11: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 11: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 3rd section front

**Throw Quantity:**

4 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

3 3rd section

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section rear

**Detent Rotational Torque Range:**

+1.500/+5.500 inch-pounds single actuator

**Contact Load Current Rating:**

1.5 amperes resistive load ac at sea level and 750.0 milliamperes inductive load ac at sea level and 300.0 milliamperes lamp load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0