

View Online at <https://aerobasegroup.com/nsn/5930-00-925-7560>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant and shock resistant

Overall Length:

1.250 inches

Overall Height:

4.950 inches

Overall Width:

1.150 inches

Body Length:

1.105 inches

Body Width:

1.150 inches

Body Height:

4.650 inches

Actuator Length:

1.060 inches

Actuator Style:

Rectangular

Actuator Height:

0.300 inches

Actuator Width:

1.060 inches

Actuator Color:

White single actuator and white single actuator and white single actuator

Illuminated Actuator Color:

Amber single actuator and green single actuator and red single actuator

Actuator Inscription:

Vert single actuator

Illuminated Actuator Color Sequence:

Upper left half of actuator green upper right half of actuator amber lower half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Holding solenoid

Nonpile-up Contact Arrangement:

5 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 300.000 milliamperes lamp ac

Special Features:

Three-way split lens

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0