

View Online at <https://aerobasegroup.com/nsn/5930-00-925-7560>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant and shock resistant

**Overall Length:**

1.250 inches

**Overall Height:**

4.950 inches

**Overall Width:**

1.150 inches

**Body Length:**

1.105 inches

**Body Width:**

1.150 inches

**Body Height:**

4.650 inches

**Actuator Length:**

1.060 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.300 inches

**Actuator Width:**

1.060 inches

**Actuator Color:**

White single actuator and white single actuator and white single actuator

**Illuminated Actuator Color:**

Amber single actuator and green single actuator and red single actuator

**Actuator Inscription:**

Vert single actuator

**Illuminated Actuator Color Sequence:**

Upper left half of actuator green upper right half of actuator amber lower half of actuator red

**Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Holding solenoid

**Nonpile-up Contact Arrangement:**

5 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 300.000 milliamperes lamp ac

**Special Features:**

Three-way split lens

**Terminal Type And Quantity:**

20 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0