# NSN 5930-00-925-7560

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-925-7560

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant and shock resistant

#### **Overall Length:**

1.250 inches

#### **Overall Height:**

4.950 inches

#### **Overall Width:**

1.150 inches

#### **Body Length:**

1.105 inches

#### **Body Width:**

1.150 inches

#### Body Height:

4.650 inches

# Actuator Length:

1.060 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.300 inches

#### Actuator Width:

1.060 inches

#### Actuator Color:

White single actuator and white single actuator and white single actuator

#### Illuminated Actuator Color:

Amber single actuator and green single actuator and red single actuator

# Actuator Inscription:

Vert single actuator

# Illuminated Actuator Color Sequence:

Upper left half of actuator green upper right half of actuator amber lower half of actuator red

# Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

# Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Holding solenoid

# Nonpile-up Contact Arrangement:

5 pole, double throw, both positions maintained single switch unit

# NSN 5930-00-925-7560

Push Switch - Page 2 of 2



### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.500

amperes inductive ac and 300.000 milliamperes lamp ac

#### **Special Features:**

Three-way split lens

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0