NSN 5930-00-926-2988

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-926-2988

Overall Length:
5.125 inches
Body Diameter:
0.625 inches
Body Length:
3.550 inches
Overall Diameter:
1.560 inches
Unthreaded Mounting Hole Diameter:
0.221 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Facility Circle Radius:
0.625 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 1500.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Features Provided:
Tamper proof cap
Contact Action Stimulus:
Contact Action Stimulus: Increase
Increase
Increase Mounting Facility Pattern:
Increase Mounting Facility Pattern: Three position circular
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range: +300.00/+750.00 actuation point degrees fahrenheit and +300.00/+750.00 deactuation point degrees fahrenheit
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range: +300.00/+750.00 actuation point degrees fahrenheit and +300.00/+750.00 deactuation point degrees fahrenheit Contact Adjustment Type:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range: +300.00/+750.00 actuation point degrees fahrenheit and +300.00/+750.00 deactuation point degrees fahrenheit Contact Adjustment Type: External deactuation point screw and external actuation point screw
Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range: +300.00/+750.00 actuation point degrees fahrenheit and +300.00/+750.00 deactuation point degrees fahrenheit Contact Adjustment Type: External deactuation point screw and external actuation point screw Contact Stimulus Rating:
Increase Mounting Facility Pattern: Three position circular Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable, preset and actuation point adjustable, preset Contact Adjustment Range: +300.00/+750.00 actuation point degrees fahrenheit and +300.00/+750.00 deactuation point degrees fahrenheit Contact Adjustment Type: External deactuation point screw and external actuation point screw Contact Stimulus Rating: 30.000 actuation point degrees fahrenheit and 299.90 deactuation point degrees fahrenheit

Gas or liquid

NSN 5930-00-926-2988

Thermostatic Switch - Page 2 of 2



Ctv/la	n Da	eian	ator:
OLYN	- 00	əiyii	atoi.

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0