

View Online at <https://aerobasegroup.com/nsn/5930-00-927-3007>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion proof and moisture proof

Overall Length:

1.810 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Body Diameter:

0.325 inches

Bushing Length:

0.310 inches

Case Material:

Metal

Actuator Diameter:

0.325 inches

Actuator Height:

0.390 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

Test Data Document:

13499-266-6810-220 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0