## NSN 5930-00-927-7312



| Rotary Switch - Page 1 of 2                                   |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-927-7312 |
| Thread Length:  |
| 0.375 inches single mounting facility                         |
| Overall Length:   |
| 1.687 inches  |
| Overall Height:   |
| 1.328 inches  |
| Overall Width:  |
| 1.297 inches  |
| Shaft Diameter:   |
| 0.248 inches single actuator and 0.250 inches single actuator |
| Shaft Length:   |
| 0.500 inches single actuator                                  |
| Nonturn Device Radius:  |
| 0.531 inches at 3: 00 o'clock                                 |
| Individual Section Quantity:                                  |
| 1   |
| Nonturn Device Type:  |
| Tab at 3: 00 o'clock  |
| Switch Contact Basic Design:                                  |
| Nonpile-up symmetrical  |
| Polo Quantity   |

Pole Quantity:

1 single section rear

**Throw Quantity:** 

3 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Clip

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-927-7312

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Clips and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A052b0