

View Online at <https://aerobasegroup.com/nsn/5930-00-928-5980>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.000 inches

Overall Height:

Between 5.000 inches and 6.250 inches

Overall Width:

2.500 inches

Distance Between Mounting Facility Centers:

2.062 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

80.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+14.70/+44.70 actuation point pounds per square inch absolute

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0