

View Online at <https://aerobasegroup.com/nsn/5930-00-929-1576>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.187 inches

Overall Height:

6.938 inches

Overall Width:

1.562 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

2.250 inches

Capillary Tube Length:

6.000 inches

Bulb Length:

4.188 inches

Bulb Diameter:

0.750 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Unthreaded hole

Features Provided:

Tubing end seal connection

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+75.00/+95.00 actuation point degrees fahrenheit and +75.00/+95.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Special Features:

0.500 in. Fitting for pipe fitting connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0