NSN 5930-00-929-1576

Hazardous Locations/environmental Protection:

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-929-1576

Dustproof
Overall Length:
3.187 inches
Overall Height:
6.938 inches
Overall Width:
1.562 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Mounting Facility Centers:
2.250 inches
Capillary Tube Length:
6.000 inches
Bulb Length:
4.188 inches
Bulb Diameter:
0.750 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Unthreaded hole
Features Provided:
Tubing end seal connection
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+75.00/+95.00 actuation point degrees fahrenheit and +75.00/+95.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

NSN 5930-00-929-1576

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 230.0 ac at sea level first voltage Special Features: 0.500 in. Fitting for pipe fitting connection Media For Which Designed: Gas Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A048b0