NSN 5930-00-929-1635

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-929-1635 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 1.796 inches **Overall Height:** 0.300 inches **Overall Width:** 0.406 inches **Bushing Length:** 0.745 inches **Body Length:** 0.906 inches **Body Width:** 0.406 inches **Body Height:** 0.300 inches **Actuator Style:** Round **Actuator Diameter:** 0.153 inches **Actuator Height:** 0.145 inches **Actuator Free Position Height:** 0.890 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.438 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 16.0 ounces **Switch Actuating Force:**

128.0 ounces

NSN 5930-00-929-1635

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

Between 0.020 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc

Thread Series Designator:

Un

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A053a0