

View Online at <https://aerobasegroup.com/nsn/5930-00-929-3111>

**Thread Length:**

0.547 inches single pressure connection

**Overall Length:**

2.344 inches

**Outside Diameter:**

0.125 inches single connection

**Body Length:**

1.000 inches

**Overall Diameter:**

1.734 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Input port

**Features Provided:**

Tamper proof cap

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

150.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

10.0 amperes resistive load third voltage and 8.0 amperes inductive load third voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

4.00 actuation point pounds per square inch and 3.50 deactuation point pounds per square inch and 1.50 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

24.0 ac at sea level second voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0