

View Online at <https://aerobasegroup.com/nsn/5930-00-929-3111>

Thread Length:

0.547 inches single pressure connection

Overall Length:

2.344 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.000 inches

Overall Diameter:

1.734 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

10.0 amperes resistive load third voltage and 8.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.00 actuation point pounds per square inch and 3.50 deactuation point pounds per square inch and 1.50 differential point pounds per square inch

Contact Voltage Rating In Volts:

24.0 ac at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0