

View Online at <https://aerobasegroup.com/nsn/5930-00-929-7407>

Hazardous Locations/environmental Protection:

Vaportight, gastight

Overall Length:

1.250 inches

Overall Height:

0.500 inches

Body Diameter:

0.640 inches

Body Height:

0.395 inches

Distance Between Mounting Facility Centers:

0.930 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

185.00 actuation point degrees fahrenheit and 170.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0