

View Online at <https://aerobasegroup.com/nsn/5930-00-929-7407>

**Hazardous Locations/environmental Protection:**

Vaportight, gastight

**Overall Length:**

1.250 inches

**Overall Height:**

0.500 inches

**Body Diameter:**

0.640 inches

**Body Height:**

0.395 inches

**Distance Between Mounting Facility Centers:**

0.930 inches

**Tempurature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

185.00 actuation point degrees fahrenheit and 170.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0