

View Online at <https://aerobasegroup.com/nsn/5930-00-929-7852>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Moisture resistant and corrosion resistant and vibration resistant and shock resistant

**Overall Length:**

0.500 inches

**Overall Height:**

1.204 inches

**Overall Width:**

0.500 inches

**Bushing Length:**

0.375 inches

**Body Length:**

0.500 inches

**Body Width:**

0.500 inches

**Body Height:**

0.328 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.078 inches

**Actuator Height:**

0.313 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc and 50.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 5.000 amperes inductive ac and 5.000 amperes resistive dc and 5.000 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0