

View Online at <https://aerobasegroup.com/nsn/5930-00-929-7852>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant and corrosion resistant and vibration resistant and shock resistant

Overall Length:

0.500 inches

Overall Height:

1.204 inches

Overall Width:

0.500 inches

Bushing Length:

0.375 inches

Body Length:

0.500 inches

Body Width:

0.500 inches

Body Height:

0.328 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Height:

0.313 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 5.000 amperes inductive ac and 5.000 amperes resistive dc and 5.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0