# NSN 5930-00-929-7858

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-929-7858

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.250 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

1.790 inches

#### Shaft Diameter:

0.127 inches single actuator

#### Shaft Length:

1.140 inches single actuator

#### **Overall Diameter:**

0.719 inches

#### Individual Section Quantity:

1

# **Operating Tempurature Range:**

-55.0/+100.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

3 single section rear

#### Throw Quantity:

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

50.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-929-7858

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

100.0 milliamperes resistive load dc at sea level

# Style Designator:

Tap, circular, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A052b0