## NSN 5930-00-930-4430

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-930-4430

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Width Between Flats:

0.188 inches single actuator

**Overall Length:** 

1.963 inches

**Overall Height:** 

1.343 inches

**Overall Width:** 

1.297 inches

First Flat Length:

0.250 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.688 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 5: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Pin at 5: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

2 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

120.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

## **NSN 5930-00-930-4430**Rotary Switch - Page 2 of 2

A052b0



Shaft Type:
Round, parallel flatted, threaded hole single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Detent Rotational Torque Range:
+1.000/+6.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: