

View Online at <https://aerobasegroup.com/nsn/5930-00-930-5016>

Body Style:

Hole mount

Body Diameter:

2.690 inches

Body Height:

1.540 inches

Unthreaded Mounting Hole Diameter:

Between 0.255 inches and 0.275 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

1.765 inches

Actuator Length:

2.500 inches

Actuator Style:

Rectangular

Actuator Height:

Between 1.900 inches and 2.350 inches

Actuator Width:

1.250 inches

Actuator Inscription:

Pull-turn single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

300.000 amperes resistive dc and 150.000 amperes inductive dc

Precious Material And Location:

Contacts silver

Test Data Document:

81349-mil-s-13625 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-s-13625/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0