## NSN 5930-00-930-5350



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-930-5350 **Thread Class:** 2b **Body Style:** Hole mount **Hazardous Locations/environmental Protection:** Dustproof and fungus resistant and waterproof **Body Diameter:** 1.812 inches **Body Height:** 0.812 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** 1.574 inches **Actuator Diameter:** 0.453 inches **Actuator Height:** 0.520 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac and 30.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded hole **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, double make, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 30.000 amperes resistive dc and 30.000 amperes resistive ac **Thread Series Designator:** Unc

Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-00-930-5350

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0