# NSN 5930-00-930-7096

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-930-7096

## **Thread Class:**

2a single mounting facility

#### Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

6.000 inches

#### **Overall Height:**

1.437 inches

#### **Overall Width:**

1.312 inches

#### First Flat Length:

0.440 inches single actuator

#### Flat Height:

0.156 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.785 inches single actuator

## Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section rear

#### **Throw Quantity:**

12 each section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### **Rotor Through Connection Quantity:**

1 each section

#### Switch Actuator Indexing Position Quantity:

12 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks each section front

# NSN 5930-00-930-7096

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### **Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

# **Precious Material And Location:**

Rotor blade surfaces and terminal surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0