NSN 5930-00-930-7096

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-930-7096

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 6.000 inches **Overall Height:** 1.437 inches **Overall Width:** 1.312 inches First Flat Length: 0.440 inches single actuator Flat Height: 0.156 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.785 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 12 each section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Rotor Through Connection Quantity:** 1 each section **Switch Actuator Indexing Position Quantity:** 12 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:**

Contact Switching Action:

Makes before breaks each section front

NSN 5930-00-930-7096

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Precious Material And Location:

Rotor blade surfaces and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0