

View Online at <https://aerobasegroup.com/nsn/5930-00-931-0252>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and moisture proof and waterproof

Overall Length:

1.310 inches

Overall Height:

1.177 inches

Overall Width:

0.750 inches

Bushing Length:

0.530 inches

Body Length:

1.310 inches

Body Width:

0.750 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.620 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

230.0 ac and 250.0 dc

Mounting Surface To Terminal End Distance:

1.062 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Test Data Document:

10001-1769715-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0