

View Online at <https://aerobasegroup.com/nsn/5930-00-931-0329>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

1.438 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Bushing Length:

0.438 inches

Body Length:

0.422 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.188 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 15.000 amperes inductive ac

Precious Material And Location:

Terminals silver

Test Data Document:

80249-840473 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0