

View Online at <https://aerobasegroup.com/nsn/5930-00-931-0516>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Driptight

**Overall Length:**

0.458 inches

**Overall Height:**

1.898 inches

**Overall Width:**

0.354 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

0.562 inches

**Body Width:**

0.354 inches

**Body Height:**

0.572 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.240 inches and 0.246 inches

**Actuator Height:**

Between 0.655 inches and 0.719 inches

**Actuator Position-action Relationship:**

Up position momentary and center position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 50.0 dc

**Mounting Surface To Terminal End Distance:**

0.706 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

3 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Test Data Document:**

81349-mil-dtl-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

96906-ms90310-271 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0