

View Online at <https://aerobasegroup.com/nsn/5930-00-931-0516>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

0.458 inches

Overall Height:

1.898 inches

Overall Width:

0.354 inches

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Body Height:

0.572 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.240 inches and 0.246 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position momentary and center position maintained and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

3 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Test Data Document:

81349-mil-dtl-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms90310-271 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0