

View Online at <https://aerobasegroup.com/nsn/5930-00-931-2622>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.624 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.125 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.213 inches single mounting facility

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

2.298 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.298 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Base single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

28.0 lowest dc voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes inductive load highest ac voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0