NSN 5930-00-931-7370



Rotary Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-931-7370 **Thread Class:** 2b single mounting facility **Overall Length:** Between 4.776 inches and 4.960 inches **Overall Height:** 2.375 inches **Overall Width:** 2.062 inches **Shaft Diameter:** 0.248 inches single actuator and 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity:** 6 **Longest Horizontal Distance Between Mounting Centers:** 1.375 inches single mounting facility **Operating Tempurature Range:** -65.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 3 each section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:**

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

NSN 5930-00-931-7370Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed-adjustable stops single actuator
Contact Load Current Rating:
2.0 amperes resistive load ac at sea level
Precious Material And Location:
Contact, wiper arm, collect ring surfaces gold and contact, wiper arm, collector ring silver
Precious Material:
Gold and silver
Style Designator:
Square wafer, panel mount
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No