

View Online at <https://aerobasegroup.com/nsn/5930-00-931-9370>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.091 inches and 0.101 inches

**Actuator Height:**

0.297 inches

**Actuator Free Position Height:**

Between 0.315 inches and 0.345 inches

**Actuator Adapter Style:**

Pushbutton

**Center To Center Distance Between Adapter Mounting Facilities Parallel To Length:**

Between 0.373 inches and 0.377 inches

**Housing Height:**

0.359 inches

**Housing Length:**

0.781 inches

**Housing Width:**

0.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

0.297 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

0.377 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0