

View Online at <https://aerobasegroup.com/nsn/5930-00-931-9370>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.091 inches and 0.101 inches

Actuator Height:

0.297 inches

Actuator Free Position Height:

Between 0.315 inches and 0.345 inches

Actuator Adapter Style:

Pushbutton

Center To Center Distance Between Adapter Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Housing Height:

0.359 inches

Housing Length:

0.781 inches

Housing Width:

0.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.297 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.377 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0