# NSN 5930-00-932-0033

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-932-0033

## Thread Class:

2a single mounting facility

#### Thread Length:

0.437 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.384 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.214 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.874 inches single actuator

**Overall Diameter:** 

1.036 inches

#### Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

### Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 3: 00 o'clock

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section front

#### **Throw Quantity:**

3 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

30.0 dc at sea level

## Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device single actuator

#### **Rotor Through Connection Quantity:**

2 each section

## NSN 5930-00-932-0033

Rotary Switch - Page 2 of 2



## Switch Actuator Indexing Position Quantity:

3 single actuator

### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

36.0 degrees single actuator

### Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

50.0 milliamperes resistive load ac at sea level

### Style Designator:

Tap, circular, bushing mount

## **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef single mounting facility

## Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A052b0