NSN 5930-00-932-2712

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-932-2712

Threa	dТ	end	ath.
IIII Ca	uL	.CIII	uui.

0.719 inches single threaded bushing

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

4.906 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.687 inches

Tempurature Sensing Element Type:

Expanding shell

Width Across Flats:

1.000 inches

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+600.00 actuation point degrees fahrenheit and -100.00/+600.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

35.00 actuation point degrees fahrenheit and 30.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

NSN 5930-00-932-2712

Thermostatic Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0