NSN 5930-00-932-6973



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-932-6973 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Body Length:** 0.510 inches **Body Width:** 0.210 inches **Body Height:** 0.350 inches **Unthreaded Mounting Hole Diameter:** 0.088 inches **Actuator Style:** Round **Actuator Diameter:** 0.063 inches **Actuator Height:** 0.030 inches **Actuator Free Position Height:** 0.320 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 1.0 ounces **Switch Actuating Force:** 5.0 ounces **Actuator Movement:** Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 5.000 amperes inductive ac **Terminal Type And Quantity:** 3 turret

Unit Of Measure:

N/a

Shelf Life:

NSN 5930-00-932-6973

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0