

View Online at <https://aerobasegroup.com/nsn/5930-00-933-0132>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Body Diameter:**

0.560 inches

**Bushing Length:**

0.250 inches

**Body Length:**

0.517 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.310 inches

**Actuator Height:**

0.313 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Test Data Document:**

97942-ja8621h17 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0