

View Online at <https://aerobasegroup.com/nsn/5930-00-934-3118>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.470 inches single mounting facility

**Overall Length:**

1.970 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.214 inches single actuator

**Shaft Diameter:**

0.251 inches single actuator

**Shaft Length:**

0.970 inches single actuator

**Overall Diameter:**

2.000 inches

**Nonturn Device Radius:**

0.372 inches at 6: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

24 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0