

View Online at <https://aerobasegroup.com/nsn/5930-00-935-9584>

**Thread Class:**

3a single pressure connection

**Overall Length:**

3.750 inches

**Outside Diameter:**

0.438 inches single connection

**Overall Diameter:**

2.250 inches

**Unthreaded Mounting Hole Diameter:**

0.204 inches

**Distance Between Mounting Facility Centers:**

0.500 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

200.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

97.00 actuation point pounds per square inch gage and 103.00 actuation point pounds per square inch gage and 10.00 deactuation point pounds per square inch gage and 13.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unjf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0