

View Online at <https://aerobasegroup.com/nsn/5930-00-935-9616>

Overall Height:

2.719 inches

Overall Width:

2.719 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.281 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

450.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Or Standard:

3sr4a2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0