

View Online at <https://aerobasegroup.com/nsn/5930-00-936-1280>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus proof and humidity resistant and dustproof and sand proof and explosion proof and salt spray resistant and shock resistant and vibration resistant and watertight

Overall Length:

2.880 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Diameter:

0.620 inches

Bushing Length:

0.250 inches

Body Length:

1.000 inches

Actuator Diameter:

0.380 inches

Actuator Height:

0.280 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0