

View Online at <https://aerobasegroup.com/nsn/5930-00-936-7567>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.378 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Overall Width:

0.406 inches

Body Length:

Between 1.347 inches and 1.409 inches

Body Width:

Between 0.391 inches and 0.421 inches

Body Height:

Between 1.090 inches and 1.152 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Length:

Between 0.766 inches and 0.828 inches

Actuator Style:

Leaf

Actuator Free Position Height:

0.645 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

Between 8.0 ounces and 16.0 ounces

Actuator Movement:

Between 0.025 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0