

View Online at <https://aerobasegroup.com/nsn/5930-00-936-7745>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

1.031 inches

Body Length:

1.200 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.295 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0