

View Online at <https://aerobasegroup.com/nsn/5930-00-936-8073>

Thread Length:

0.375 inches single mounting facility

Width Between Flats:

0.216 inches single actuator

Overall Length:

2.547 inches

Overall Height:

1.625 inches

Overall Width:

1.031 inches

First Flat Length:

0.375 inches single actuator

Shaft Length:

0.500 inches single actuator

Nonturn Device Radius:

0.516 inches at 5:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 5:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

5 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

28.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0