

View Online at <https://aerobasegroup.com/nsn/5930-00-937-2137>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

0.562 inches

**Overall Height:**

1.359 inches

**Overall Width:**

0.408 inches

**Bushing Length:**

0.170 inches

**Body Length:**

0.562 inches

**Body Width:**

0.354 inches

**Actuator Style:**

Round

**Actuator Height:**

0.440 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.749 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Special Features:**

Black oxide finish on actuator, bushing, and facenut

**Precious Material And Location:**

Terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0