

View Online at <https://aerobasegroup.com/nsn/5930-00-937-9012>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Bushing Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.570 inches

Body Height:

0.625 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.328 inches

Actuator Position-action Relationship:

Down position maintained and up position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes resistive ac and 2.500 amperes inductive ac and 2.400 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0