

View Online at <https://aerobasegroup.com/nsn/5930-00-937-9016>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

1.475 inches

**Overall Height:**

2.094 inches

**Overall Width:**

1.475 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.300 inches

**Body Width:**

1.300 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.686 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained and left position momentary and right position momentary

**Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.938 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary 4th switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

24 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0