

View Online at <https://aerobasegroup.com/nsn/5930-00-937-9016>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

1.475 inches

Overall Height:

2.094 inches

Overall Width:

1.475 inches

Bushing Length:

0.470 inches

Body Length:

1.300 inches

Body Width:

1.300 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.686 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained and left position momentary and right position momentary

Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.938 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary 4th switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0