NSN 5930-00-938-5076

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-938-5076

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.980 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.250 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 11 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 11 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-938-5076

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 450.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0